

## **Tech Bulletin May 1, 2018**

### **2018 SLINGER BEES**

**FUEL TANK:** If stock fuel tank is ahead of the rear axle it may remain in that location. If the fuel tank is behind the rear axle, it must be replaced with a fuel cell or a boat tank (6.6 gal. Maximum) securely mounted in the trunk by no less than 4 1" x 1/8" steel straps with 3/8" hardware (no plumber's hardware). Fuel line must exit the top of the tank. Fuel cell must have steel exterior container. Fuel line cannot run thru driver's compartment

Stock air cleaner, Stock K&N Replacement, or K&N cone style allowed or Slinger Speedway approved aftermarket filter allowed.

### **2018 SLINGER SUPER**

#### **BEES**

**FUEL CONTAINER--** Fuel cell (8-gal. Max.), complete with steel container, foam baffling and check valve required. Minimum 11-gauge steel container. Fuel container must be mounted in trunk behind rear axle, as far forward as possible, above frame. No part of the fuel cell may extend below the unibody frame rail in the trunk area of the car. Filler tube extensions not allowed. All vents must be valved to eliminate leakage. Fuel container installation will be vigorously inspected. Steel fuel lines must be properly located outside driver's compartment. Rear fuel cell protection (ASA) bar required. Gasoline only.